

Sacramento Valley Groundwater Basin North American Subbasin

- Groundwater Basin Number: 5-21.64
- County: Sutter, Placer, Sacramento
- Surface Area: 351,000 acres (548 square miles)

Basin Boundaries and Hydrology

The North American subbasin lies in the eastern central portion of the Sacramento Groundwater Basin. The Bear River is its northern boundary, the Feather River is its western boundary, and the Sacramento River is its southern boundary. The eastern boundary is a north-south line extending from the Bear River south to Folsom Lake, which passes about 2 miles east of the town of Lincoln. The eastern boundary represents the approximate edge of the alluvial basin, where little or no groundwater flows into or out of the groundwater basin from the rock of the Sierra Nevada (DWR 1997). The eastern portion of the study area is characterized by low rolling dissected uplands. The western portion is nearly a flat flood basin for the Bear, Feather, Sacramento and American rivers, and several small east side tributaries. The general direction of drainage is west-southwest at an average grade of about 5 percent.

Precipitation ranges from 18-20 inches in the western half of the subbasin to 20-24 inches in the eastern half of the subbasin.

Hydrogeologic Information

The following geologic references are presented in Feasibility Report, American Basin Conjunctive Use Project by California Department of Water Resources (1997).

Water Bearing Formations

The water-bearing materials of the North American subbasin are dominated by unconsolidated continental deposits of Late Tertiary and Quaternary age. Deposits include Miocene/Pliocene volcanics, older alluvium, and younger alluvium. The alluvium can be characterized as comprising the upper aquifer system, occupying the upper 200 to 300 feet below ground surface; the Mehrten and older geologic units can be characterized as comprising the lower aquifer system, occurring generally deeper than 300 feet towards the west side of the subbasin. The cumulative thickness of these deposits increases from a few hundred feet near the Sierra Nevada foothills on the east to over 2,000 feet along the western margin of the subbasin. Most of the groundwater is produced in the northern portion of the subbasin. The aquifer zones in the upper 200 to 300 feet of this portion of the subbasin appear to be unconfined and behave similarly to stresses imposed on them. Conversely, deeper zones show a delayed response to stresses in the upper zone, indicating possibly limited interconnection with the shallower zones (DWR 1997).

Younger Alluvium. These deposits include flood basin deposits and recent stream channel deposits. The flood basin deposits occur along the western margin of the subbasin adjacent to the Sacramento River. The flood basin

deposits consist primarily of silts and clays, although they may be locally interbedded with stream channel deposits of the Sacramento River. Thickness of the unit ranges from 0 to 100 feet. Because of the fine-grained nature, the flood basin deposits have low permeability and generally yield low quantities of water to wells. Brackish water is often encountered in these deposits.

The stream channel deposits include sediments deposited in the channels of active streams as well as overbank deposits of those streams, terraces, and local dredge tailings. These deposits occur predominantly along the Sacramento and American Rivers and their major tributaries, and consist primarily of unconsolidated silt, fine- to medium-grained sand, and gravel. Thickness of the unit ranges from 0 to about 100 feet. Sand and gravel zones in the younger alluvium are highly permeable and yield significant quantities of water to wells.

Older Alluvium. These deposits consist of loosely to moderately compacted sand, silt, and gravel deposited in alluvial fans during the Pliocene and Pleistocene. A number of formational names have been assigned to the older alluvium, including the Modesto, Riverbank, and Turlock Lake Formations (Helley and Harwood 1985), Victor and Laguna Formations (Olmstead and Davis 1961), and Arroyo Seco Gravels, South Fork Gravels, and Fair Oaks Formation (DWR 1974). The older alluvial units are widely exposed between the Sierra Nevada foothills and overlying younger alluvial units near the axis of the Sacramento Valley. Thickness of the older alluvium ranges between 100 to 650 feet. It is moderately permeable.

Miocene/Pliocene Volcanics. These deposits consist of the Mehrten Formation, a sequence of fragmented volcanic rocks. The Mehrten Formation is exposed along the eastern margin of the subbasin between the towns of Lincoln and Folsom. It is composed of intervals of "black sands," stream gravels, silt, and clay interbedded with intervals of dense tuff breccia. The sand and gravel intervals are highly permeable and wells completed in them have reported yields of over 1,000 gpm. The tuff breccia intervals act as confining layers. Thickness of the unit is between 200 and 1,200 feet.

Groundwater Level Trends

Groundwater levels in southwestern Placer County and northern Sacramento County have generally decreased, with many wells experiencing declines at a rate of about one and one-half feet per year for the last 40 years or more (PCWA1999). Some of the largest decreases have occurred in the area of the former McClellan AFB. Groundwater levels in Sutter and northern Placer Counties generally have remained stable, although some wells in southern Sutter County have experienced declines (DWR 1997).

Groundwater Storage

Groundwater Storage Capacity. DWR (1997) assumed a specific yield of 7% and an aquifer thickness of 200 feet for 200,000 acres within the North American subbasin. Storage capacity can be estimated for the North American subbasin by applying the same assumptions as DWR (1997) – specific yield of 7% and an assumed thickness of 200 feet over the entire

351,000 acre subbasin. This results in an estimated storage capacity of approximately 4.9 million acre-feet.

Groundwater in Storage. There are no known published reports that discuss groundwater in storage.

Groundwater Budget (Type B)

As part of its water planning process, DWR estimated the following components of the groundwater budget. The calculations are for a 1990 level of development. Estimated inflows include natural recharge at 83,800 acre-feet and applied water recharge at 29,800 acre-feet. There was no artificial recharge. Estimated outflows include urban extraction at 109,900 acre-feet and agricultural extraction at 289,100 acre-feet.

Groundwater Quality

Characterization. The chemistry and quality of groundwater has been assessed for the American Basin. Many areas of good quality groundwater exist in the North American subbasin. In some portions of the basin groundwater quality is marginal. The three major groundwater types are: magnesium calcium bicarbonate or calcium magnesium bicarbonate; magnesium sodium bicarbonate or sodium magnesium bicarbonate; and sodium calcium bicarbonate or calcium sodium bicarbonate (DWR 1997).

Comparison of groundwater quality data with applicable water quality standards and guidelines for drinking and irrigation indicate elevated levels of TDS/specific conductance, chloride, sodium, bicarbonate, boron, fluoride, nitrate, iron manganese, and arsenic may be of concern in some locations within the subbasin (DWR 1997).

High TDS levels exist in an area along the Sacramento River extending from Sacramento International Airport northward to the Bear River. The highest levels of TDS are found in an area extending just south of Nicholas to Verona, between Reclamation District 1001 and the Sutter Bypass. Some wells in this area have reported TDS exceeding 1,000 mg/L.

This same area along the Sacramento River extending from Sacramento International Airport northward to the Bear River also contains high levels of chloride, sodium, bicarbonate, manganese, and arsenic. The groundwater in the southern part of the basin is generally characterized as good quality, low in disinfection by-product precursor materials and moderate in mineral content, although some localized contamination issues do exist.

Impairments. There are three sites within the subbasin with significant groundwater contamination issues: the former McClellan AFB, Union Pacific Railroad Rail Yard in Roseville and the Aerojet Superfund Site. Although the Aerojet site lies south of the North American subbasin, a contaminant plume (including TCE and PCE) extends north from Aerojet, under the American River and into the North American subbasin (Montgomery Watson 2000). Other localized areas of contamination exist throughout the basin and are generally smaller in scope and extent of contamination.

Water Quality in Public Supply Wells

Constituent Group ¹	Number of wells sampled ²	Number of wells with a concentration above an MCL ³
Inorganics – Primary	265	7
Radiological	254	2
Nitrates	276	0
Pesticides	268	0
VOCs and SVOCs	267	6
Inorganics – Secondary	265	75

¹ A description of each member in the constituent groups and a generalized discussion of the relevance of these groups are included in *California's Groundwater – Bulletin 118* by DWR (2003).

² Represents distinct number of wells sampled as required under DHS Title 22 program from 1994 through 2000.

³ Each well reported with a concentration above an MCL was confirmed with a second detection above an MCL. This information is intended as an indicator of the types of activities that cause contamination in a given basin. It represents the water quality at the sample location. It does not indicate the water quality delivered to the consumer. More detailed drinking water quality information can be obtained from the local water purveyor and its annual Consumer Confidence Report.

Well Characteristics

	Well yields (gal/min)	
Municipal/Irrigation	Range: 752-2,500	Average: 800 (DWR 1997)
	Total depths (ft)	
Domestic	Range: 50-1,750	Average: 190 (665 well completion reports)
Municipal/Irrigation	Range: 77-1,025	Average: 396 (105 well completion reports)

Active Monitoring Data

Agency	Parameter	Number of wells /measurement frequency
DWR	Groundwater levels	53 wells semi-annually, 7 monthly
Sacramento County		17 wells semi-annually
South Sutter WD		21 wells semi-annually, 1 monthly
Sutter County		22 wells semi-annually
DWR	Mineral, nutrient, & minor element.	32 wells biennially
Department of Health Services (including co-operators)	Title 22	Approximately 275 wells

Basin Management

Groundwater management:	<p>The Sacramento Groundwater Authority (SGA) is a joint powers authority responsible for the protection of the regional groundwater basin within Sacramento County north of the American River. SGA adopted a groundwater management plan on December 11, 2003.</p> <p>South Sutter WD adopted an AB 3030 plan in 1995.</p> <p>Placer County Water Agency adopted an AB 3030 plan in 1998 and updated this plan in 2003.</p> <p>City of Lincoln adopted a groundwater management plan on November 12, 2003.</p>
Water agencies	
Public	<p>South Sutter WD, Camp Far West ID, Rio Linda/Elverta CWD, Citrus Heights WD, San Juan Suburban WD, Fair Oaks WD, Carmichael WD, Sacramento Suburban WD, Western Placer ID, Placer County WA, Del Paso Manor WD, City of Sacramento WSA, City of Roseville, Sacramento County Water Agency</p>
Private	<p>Pleasant Grove – Verona MWC, Natomas Central MWC, California-American WC, Orangevale WC, Southern California WC,</p>

Selected Bibliography

- Berkstresser, C.F. Jr. 1973. *Base of Fresh Ground-Water --* Approximately 3,000 micromhos -- in the Sacramento Valley and Sacramento-San Joaquin Delta, California. U.S. Geological Survey Water-Resource Inv. 40-73.
- Bertoldi, G.L. 1974. *Estimated Permeabilities for Soils in the Sacramento Valley*, California. U.S. Geological Survey Water-Resources Investigations Report 51-73.
- Bertoldi, G.L., Johnston, R.H., and K.D. Evenson. 1991. *Ground Water in the Central Valley, California – A Summary Report*. U.S. Geological Survey Professional Paper 1401-A.
- Bryan, Kirk. 1923. *Geology and Ground-Water Resources of the Sacramento Valley*, California. U.S. Geological Survey Water-Supply Paper 495. 1923.
- California Department of Water Resources. 1974. *Evaluation of Ground Water Resources: Sacramento County*. Bulletin 118-3. July 1974.
- California Department of Water Resources. 1978. *Evaluation of Ground Water Resources: Sacramento Valley*. Bulletin 118-6. August 1978.
- California Department of Water Resources. 1997. *Feasibility Report, American Basin Conjunctive Use Project*. June 1997.
- California Department of Water Resources. 1999. *Groundwater Management in California*.
- California Department of Water Resources. 1990. *Historical Ground Water Levels in Sacramento County*. November 1990.
- California Department of Water Resources. 1991. *Historical Ground Water Levels in Placer County*. May 1991.
- California Department of Water Resources. 1992. *Historical Ground Water Levels in Sutter County*. February 1992.

- Fogelman, R.P and Rockwell, G.L. 1977. *Descriptions and Chemical Analyses for selected wells in the Eastern Sacramento Valley*, California. U.S. Geological Survey Open-File Report 77-486.
- Fogelman, R.P. 1979. *Chemical Quality of Ground Water in the Eastern Sacramento Valley*, California. U.S. Geological Survey Water-Resource Investigations Report 78-124.
- Harwood, D.S., and Helley, E.J. 1987. *Late Cenozoic Tectonism of the Sacramento Valley*, California. U.S. Geological Survey Professional Paper 1359.
- Helley, E.J., and Harwood, D.S. 1985. *Geologic Map of the Late Cenozoic Deposits of the Sacramento Valley and Northern Sierran Foothills*, California. U.S. Geological Survey Miscellaneous Field Studies Map MF-1790.
- Montgomery Watson in Association with Navigant Consulting and CH2M-Hill. 2000. *American River Basin Cooperating Agencies, Regional Water Master Plan, Phase II Report, Technical Memoranda –DRAFT*. June 28, 2000.
- Olmstead, F.H., and Davis, G.H. 1961. *Geologic Features and Ground-Water Storage Capacity of the Sacramento Valley*, California. U.S. Geological Survey Water-Supply Paper 1497.
- Page, R.W. 1974. *Base and Thickness of the Post-Eocene Continental Deposits in the Sacramento Valley*, California. U.S. Geological Survey Water-Resource Investigations Report 45-73.
- Page, R.W. 1986. *Geology of the Fresh Ground-Water Basin of the Central Valley*. California, with Texture Maps and Sections. U.S. Geological Survey Professional Paper 1401-C.
- Placer County Water Agency and Northridge Water District. 1999. *Groundwater Stabilization Project, Final Environmental Impact Report*. February

Errata

Updated groundwater management information and added hotlinks to applicable websites.
(1/20/06)